



Functionality in a wide range of applications:
We offer a solution for every requirement.

www.wago.com/relays-and-optocouplers

Series	Input Nominal Voltage	Limiting Continuous Current						AU					ANSI/ISA		Item Number						
2042 Series (10.4 ... 26 mm wide)																					
	24 VDC	6 A	-40 ... +70 °C	1	1										2042-3004						
		8 A			2										2042-3014						
		5 A			4										2042-3024						
		10 A				1									2042-3034						
		8 A				2									2042-3044						
		6 A			1										2042-3054						
		8 A			1	1									2042-3064						
		5 A			1	3									2042-3074						
		5 A			2	2									2042-3084						
	24 ... 230 V AC/DC	3 A	-40 ... +50 °C	1	1										2042-3809						
		5 A			2										2042-3819						
		3 A			4										2042-3829						
		4 A				1									2042-3839						
		5 A				2									2042-3849						
		6 A			1										2042-3859						
		5 A			1	1									2042-3869						
		3 A			1	3									2042-3879						
		3 A			2	2									2042-3889						
857 Series Timer Relays (6 mm wide)																					
	24 VDC	6 A	-25 ... +70 °C	1											857-604						
															857-640						
															857-642						
859 Series (6 mm wide)																					
	5 VDC	5 A	-40 ... +50 °C	1											859-302						
	12 VDC														859-312						
	12 VAC/DC															859-303					
	24 VDC	5 A	-40 ... +70 °C												859-353						
															859-390						
															859-392						
															859-398						
	24 VAC/DC	3 A	-40 ... +50 °C												859-304						
															859-314						
															859-354						
	36 VDC	3 A													859-386						
	48 VDC														859-394						
	48 VAC/DC														859-397						
	60 VAC/DC	5 A	-40 ... +70 °C												859-355						
	72 VDC	3 A													859-356						
	110 VDC														859-393						
															859-399						
															859-391						
	115 VAC/DC	5 A													859-317						
																859-357					
																859-360					
	115 VAC															859-367					
	220 VDC	5 A													859-318						
	230 VAC/DC													859-358							
															859-359						
	230 VAC															859-368					

Series	Input Nominal Voltage	Limiting Continuous Current						AU					ANSI/ISA		Item Number									
857 Series (6 mm wide)																								
	24 ... 230 V AC/DC	6 A	-40 ... +70 °C			1									857-359									
	12 VDC																	857-369						
	24 VDC		-40 ... +60 °C													857-303								
	24 VAC/DC	4 A													857-304									
	115 VAC/DC															857-314								
	230 VAC/DC																	857-1330						
	230 VAC	6 A													857-354									
																	857-357							
																		857-358						
788 Series (15 mm wide)																								
	12 VDC	8 A	-40 ... +70 °C			2										788-311								
		16 A				1												788-303						
	24 VDC	0.3 A	-40 ... +60 °C			2											788-353							
		8 A	-40 ... +70 °C																788-906*					
		6 A	-25 ... +70 °C																788-312					
		8 A	-40 ... +70 °C														788-412							
		8 A																	788-346					
		8 A																	788-384*					
		16 A																	788-390					
		16 A																	788-357					
	24 VAC	8 A	1																788-354					
		16 A																	788-304					
		8 A																	788-404					
		16 A																	788-391					
	48 VDC	8 A	2																788-341					
		16 A																	788-512					
		8 A																	788-546					
		16 A																	788-506					
	60 VDC	8 A	2																788-541					
		16 A																	788-313					
		8 A																	788-305					
		16 A																	788-314					
	110 VDC	8 A	1																788-315					
		16 A																	788-306					
		8 A																	788-315					
		16 A																	788-307					
	115 VAC	8 A	2																788-515					
		16 A																	788-548					
		8 A																	788-615					
		16 A																	788-507					
	230 VAC	8 A	2																788-607					
		16 A																	788-543					
		8 A																	788-516					
		16 A																	788-616					
	230 VAC	8 A	2																788-549					
		16 A																	788-508					
		8 A																	788-608					
		16 A																	788-544					
858 Series (31 mm wide)																								
	12 VDC	5 A	-25 ... +70 °C			4										858-303								
	24 VDC																				858-304			
																					858-314			
																					858-354			
	24 VAC						-40 ... +70 °C														858-355			
																				858-390				
																				858-324				
																				858-504				
	48 VDC						-25 ... +70 °C														858-514			
																				858-305				
																				858-325				
																				858-307				
	110 VDC						-40 ... +55 °C														858-392			
																				858-327				
																				858-507				
																				858-517				
	115 VAC						-25 ... +70 °C														858-308			
																				858-391				
																				858-328				
																				858-508				
	230 VAC						-40 ... +70 °C														858-518			
																				858-528				
																				858-508				
																				858-518				

*Force-guided contacts